



Product information

Sonis

Rear table panels (H=60 cm) suspended from the table top.





Table pane I for suspended mounting, on the table top or, in the case of sliding table tops, on the table crossbar. Can be used as a privacy screen and acoustic element. Table panels can be positioned at the side or at the rear edge of the table and connected to each other across corners using adapters.

Installation: Rear table panels increase the table's footprint, but the geometry of the work surface remains unchanged. For height-adjustable tables, a distance of 2.5 cm from other objects must be maintained.

Support plate in sandwich construction with a honeycomb core, covered on both sides with fabric-covered cover plates made of compressed polyester fibre. The panels are available in square (Fig. I) or rounded (Fig. II) versions, in thicknesses of 2.8 or 5.5 cm. Without accent strips (Fig. I, II) or with black accent strips (Fig. III, IV).

Sound absorber classes C (2.8 cm) and B (5.5 cm) were measured and certified as free-standing in accordance with DIN EN ISO 354:2003 and DIN EN ISO 11654:1997. Organisational accessories have only a limited acoustic effect.

The following material groups are available: Fabric cover: S51,74,78,84; Stabiliser and foot made of steel: M(black, white).

	Height from tabletop to top edge of screen: 15.75 in										
											
Sonis	Acoustic type		C Absorber								
	h = 23.65 in		05070	05071	05072	05073	05074	05075	05076	05077	05078
	d in		Panel thickness 1.15 / Total 1.35								
	Acoustic type		B Absorber								
	h = 23.65 in		05170	05171	05172	05173	05174	05175	05176	05177	05178
	d in		Panel thickness 2.2 / Total 2.45								
	w in		47.25	55.15	63	70.9	78.75	47.25	55.15	63	23.65